

Loctite 7063

# Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 6

sds no.: 179512

V001.7 Revision: 14.10.2009

printing date: 25.11.2009

## 1. Identification of the substance/preparation and of the company/undertaking

#### Trade name:

Loctite 7063

#### Intended use:

Solvent based cleaner

### Company name:

Henkel AG & Co. KGaA

Henkelstr. 67

40191 Düsseldorf

Germany

Phone: +49 (211) 797-0

## E-mail address of person responsible for Safety Data Sheet:

ua-productsafety.uk@uk.henkel.com

## **Emergency information:**

24 Hours Emergency Tel: +44 (0)20 8312 0291

## 2. Hazards identification

R11 Highly flammable.

R38 Irritating to skin.

R67 Vapours may cause drowsiness and dizziness.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The aerosol container is under pressure. Do not expose to high temperatures.

## 3. Composition / information on ingredients

### General chemical description:

Solvent cleaner

## Declaration of ingredients according to (EC) No 1907/2006:

Hazardous components	EINECS	content	Classification
CAS-No.	ELINCS		
Ethanol denatured	200-578-6	10 - 20 %	F - Highly flammable; R11
64-17-5			
Methylal	203-714-2	10 - 20 %	F - Highly flammable; R11
109-87-5			
Naphtha, hydrotreated light, <0,1%	265-151-9	50 - 70 %	F - Highly flammable; R11
benzene			Xn - Harmful; R65
64742-49-0			Xi - Irritant; R38
			R67
			N - Dangerous for the environment; R51/53
Carbon dioxide	204-696-9	1 - 10 %	No classification required.
124-38-9			

MSDS-No.: 179512 Loctite 7063 Page 2 of 6

V001.7

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

### 4. First aid measures

#### Inhalation:

Move to fresh air.

Seek medical advice.

#### Skin contact:

Rinse with running water and soap.

Seek medical advice.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

### **Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

## 5. Fire fighting measures

#### **Combustion behaviour:**

Solvent containing flammable product. In case of fire toxic gases are released.

#### Suitable extinguishing media:

foam, extinguishing powder, carbon dioxide.

### Special protection equipment for firefighters:

Wear self-contained breathing apparatus.

## Special hazards by the product itself:

Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

### **Hazardous combustion products:**

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

#### Additional information:

In case of fire, keep containers cool with water spray.

## 6. Accidental release measures

## **Personal precautions:**

Remove sources of ignition.

Ensure adequate ventilation.

### **Environmental precautions:**

Do not let product enter drains.

### Clean-up methods:

Wipe up using absorbent material

Store in a partly filled, closed container until disposal.

## 7. Handling and storage

## Handling:

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

Use only in well-ventilated areas.

MSDS-No.: 179512 Loctite 7063 Page 3 of 6

V001.7

### Storage:

Store in a cool, dry place.

Do not store near sources of heat or ignition, or reactive materials.

## 8. Exposure controls / personal protection

## Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Туре	Category	Remarks
ETHANOL	1.000	1.920	Time Weighted Average		EH40 WEL
64-17-5			(TWA).		
DIMETHOXYMETHANE	1.250	3.950	Short Term Exposure		EH40 WEL
109-87-5			Limit (STEL):		
DIMETHOXYMETHANE	1.000	3.160	Time Weighted Average		EH40 WEL
109-87-5			(TWA).		
CARBON DIOXIDE	15.000	27.400	Short Term Exposure		EH40 WEL
124-38-9			Limit (STEL):		
CARBON DIOXIDE	5.000	9.150	Time Weighted Average		EH40 WEL
124-38-9			(TWA).		

### **Respiratory protection:**

Do not inhale vapors and fumes. Use only in well-ventilated areas.

### Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.

In circumstances where there is a potential for prolonged or repeated skin contact, the use of disposable gloves (polyethylene, natural rubber or equivalent ester-resistant material) is recommended.

### Eye protection:

Wear protective glasses.

### Skin protection:

Suitable protective clothing

## General protection and hygiene measures:

Good industrial hygiene practices should be observed.

## 9. Physical and chemical properties

General characteristics:

Appearance aerosol colourless
Odor: hydrocarbons

Phys./chem. properties:

pH-value Not applicable

Boiling point 87 - 104 °C (188.6 - 219.2 °F)

Flash point -21 °C (-5.8 °F)
Density 0,742 g/cm3

Solubility (qualitative) Not miscible

(Solvent: Water)

Solubility (qualitative) Miscible

(Solvent: Acetone)

VOC content 95 %

(1999/13/EC)

()

MSDS-No.: 179512 Loctite 7063 Page 4 of 6

V001.7

## 10. Stability and reactivity

### Conditions to avoid:

Stable under normal conditions of storage and use. Heat, flames, sparks and other sources of ignition.

#### Materials to avoid:

Strong oxidizing agents.

### Hazardous decomposition products:

None if used for intended purpose.

## 11. Toxicological information

## Oral toxicity:

Harmful if swallowed.

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

#### Inhalative toxicity:

May cause headache and dizziness.

#### Skin irritation:

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals. Irritating to the skin.

#### Eye irritation:

May cause mild irritation to the eyes.

## 12. Ecological information

### **Ecotoxicity:**

Toxic to aquatic organisms

May cause long-term adverse effects in the aquatic environment.

Do not empty into drains / surface water / ground water.

## **Mobility:**

The product evaporates readily.

### Persistence and Biodegradability:

No data available.

## **Bioaccumulative potential:**

No data available.

### **Ecotoxicity:**

Hazardous components	Species	Exposure	Value	Value
CAS-No.		time	type	
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	Ide, silver or golden orfe (Leuciscus idus)	48 h	LC 50	> 1 - 10 mg/l

## 13. Disposal considerations

### Product disposal:

Dispose of according to regulations.

### Waste code(EWC):

140603

MSDS-No.: 179512 Loctite 7063 Page 5 of 6

V001.7

### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

## 14. Transport information

## Road transport ADR:

Class: 2

Packaging group:

Classification code: 5F

Hazard ident. number:

UN no.: 1950 Label: 2.1

Technical name: AEROSOLS

### Railroad transport RID:

Class: 2

Packaging group:
Classification code: 5F
Hazard ident. number: 23
UN no.: 1950
Label: 2.1

Technical name: AEROSOLS

## Inland water transport ADN:

Class: 2

Packaging group:

Classification code: 5F

Hazard ident. number:

UN no.: 1950 Label: 2.1

Technical name: AEROSOLS

## Marine transport IMDG:

Class: 2.1

Packaging group:

UN no.: 1950 Label: 2.1 EmS: F-D ,S-U

Seawater pollutant:

Proper shipping name: AEROSOLS

### Air transport IATA:

Class: 2.1

Packaging group:

Packaging instructions (passenger) 203
Packaging instructions (cargo) 203
UN no.: 1950
Label: 2.1

Proper shipping name: Aerosols, flammable

MSDS-No.: 179512 Loctite 7063 Page 6 of 6

V001.7

## 15. Regulations - classification and identification

### **Indication of danger:**

F - Highly flammable

N - Dangerous for the environment

Xi - Irritant







### Risk phrases:

R11 Highly flammable.

R38 Irritating to skin.

R67 Vapours may cause drowsiness and dizziness.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Safety phrases:

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe spray.

S24 Avoid contact with skin.

S51 Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

## Additional labeling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children

## 16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicted by codes in this safety data sheet are as follows:

R11 Highly flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

### **Further information:**

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.