



Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 6

Loctite(R) 620 Retaining Compound Slip Fit

SDS no. : 153472
V001.3

Revision: 04.11.2008
printing date: 25.11.2009

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

Loctite(R) 620 Retaining Compound Slip Fit

Intended use:

Anaerobic

Company name:

Henkel AG & Co. KGaA
Henkelstr. 67
40191 Düsseldorf

Germany

Phone: +49 (211) 797-0

E-mail address of person responsible for Safety Data Sheet:

ua-productsafety.uk@uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44 (0)20 8312 0291

2. Hazards identification

Relevant routes of exposure:

Product contains N,N-(m-phenylene)dimaldimide which is very toxic by inhalation In this product it is present in the wetted form and does not pose an inhalation hazard.

R41 Risk of serious damage to eyes.
R37/38 Irritating to respiratory system and skin.
R43 May cause sensitization by skin contact.

3. Composition / information on ingredients

General chemical description:

Anaerobic Sealant

Declaration of ingredients according to EC/1907/2006:

Hazardous components CAS-No.	EINECS ELINCS	content	Classification
Bisphenol A -methacrylateoethyl ether 24448-20-2	246-263-7	> 70 - < 80 %	Xi - Irritant; R36/37/38
N,N-(m-phenylene)dimaldimide 3006-93-7	221-112-8	> 10 - < 20 %	T+ - Very toxic; R26 Xi - Irritant; R38 Xi - Irritant; R41 Xi - Irritant; R43
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	248-666-3	> 1 - < 5 %	Xi - Irritant; R36, R43
Cumene hydroperoxide 80-15-9	201-254-7	> 1 - < 3 %	O - Oxidizing; R7 T - Toxic; R23 N - Dangerous for the environment; R51, R53 Xn - Harmful; R21/22, R48/20/22 C - Corrosive; R34
Cumene 98-82-8	202-704-5	> 0,1 - < 0,5 %	Xn - Harmful; R65 Xi - Irritant; R37 R10 N - Dangerous for the environment; R51, R53
N,N-dimethyl-o-toluidine 609-72-3	210-199-8	> 0,1 - < 0,5 %	T - Toxic; R23/24/25 R52, R53 R33

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

Carbon dioxide, foam, powder

Special protection equipment for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:

Oxides of carbon, oxides of nitrogen, irritating organic vapors., Sulphur oxides

6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

7. Handling and storage**Handling:**

Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

8. Exposure controls / personal protection**Components with specific control parameters for workplace:**

Valid for
Great Britain
Basis
UK EH40 WELs

Ingredient	ppm	mg/m3	Type	Category	Remarks
CUMENE 98-82-8	20	100	Time Weighted Average (TWA).		EU-2000/39/EC
CUMENE 98-82-8	50	250	Short Term Exposure Limit (STEL):		EU-2000/39/EC
CUMENE 98-82-8			Skin designation:	Can be absorbed through the skin.	EU-2000/39/EC
CUMENE 98-82-8	25	125	Time Weighted Average (TWA).		EH40 WEL
CUMENE 98-82-8	50	250	Short Term Exposure Limit (STEL):		EH40 WEL
CUMENE 98-82-8			Skin designation:	Can be absorbed through the skin.	EH40 WEL

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

General protection and hygiene measures:

Good industrial hygiene practices should be observed.

9. Physical and chemical properties

General characteristics:

Appearance	liquid Green
Odor:	Characteristic

Phys./chem. properties:

Boiling point	> 150 °C (> 302 °F)
Flash point	> 93,3 °C (> 199.94 °F)
Vapor pressure (20 °C (68 °F))	< 0,1 mbar
Density (20 °C (68 °F))	1,16 g/cm ³
Solubility (qualitative) (Solvent: Water)	Slight
Solubility (qualitative) (Solvent: Acetone)	Not miscible
VOC content (1999/13/EC)	< 3 %

10. Stability and reactivity

Conditions to avoid:

Stable

Materials to avoid:

Reaction with strong acids.
Reacts with strong oxidants.

11. Toxicological information

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

Irritating to respiratory system

Skin irritation:

Irritating to the skin.

Eye irritation:

Risk of serious damage to eyes

Sensitizing:

May cause sensitization by skin contact.

12. Ecological information

Mobility:

Cured adhesives are immobile.

General ecological information:

Do not empty into drains / surface water / ground water.
Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

13. Disposal considerations

Product disposal:

Dispose of in accordance with local and national regulations.
Contribution of this product to waste is very insignificant in comparison to article in which it is used

Waste code():

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulations - classification and identification

Indication of danger:

Xi - Irritant



Contains

Methacrylic acid, monoester with propane-1,2-diol,
N,N-(m-phenylene)dimalimide

Risk phrases:

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitization by skin contact.

Safety phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water and soap.

S37/39 Wear suitable gloves and eye/face protection.

S51 Use only in well-ventilated areas.

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicated by codes in this safety data sheet are as follows:

- R10 Flammable.
- R21/22 Harmful in contact with skin and if swallowed.
- R23 Toxic by inhalation.
- R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
- R26 Very toxic by inhalation.
- R33 Danger of cumulative effects.
- R34 Causes burns.
- R36 Irritating to eyes.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R43 May cause sensitization by skin contact.
- R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
- R51 Toxic to aquatic organisms.
- R52 Harmful to aquatic organisms.
- R53 May cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R7 May cause fire.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and its subsequent amendments, and Commission Directive 1999/45/EC.