

Loctite 640

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 5

SDS no.: 173097

V001.2 Revision: 11.09.2007

printing date: 25.11.2009

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

Loctite 640

Intended use:

Anaerobic

Company name:

Henkel AG & Co. KGaA

Henkelstr. 67

40191 Düsseldorf

Germany

Phone: +49 (211) 797-0

E-mail address of person responsible for Safety Data Sheet:

ua-productsafety.uk@uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44(0)8701906777

2. Hazards identification

Non corrosive to skin in accordance with the in vitro test method, B40 Skin Corrosion - Human skin model assay, specified in Part B of Annex V to Directive 67/548/EEC.

R41 Risk of serious damage to eyes.

R37/38 Irritating to respiratory system and skin.

R43 May cause sensitization by skin contact.

3. Composition / information on ingredients

General chemical description:

Methacrylate resin based product containing Acrylic Acid

Declaration of ingredients according to EC/1907/2006:

MSDS-No.: 173097 Loctite 640 Page 2 of 5

V001.2

Hazardous components CAS-No.	EINECS ELINCS	content	Classification	
Hydroxypropyl methacrylate 27813-02-1	248-666-3	> 5 - < 10 %	Xi - Irritant; R36, R43	
Acrylic acid 79-10-7	201-177-9	> 5 - < 10 %	R10 Xn - Harmful; R20/21/22 C - Corrosive; R35 N - Dangerous for the environment; R50	
Cumene hydroperoxide 80-15-9	201-254-7	> 1 - < 3 %	O - Oxidizing; R7 T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 C - Corrosive; R34 N - Dangerous for the environment; R51, R53	
Cumene 98-82-8	202-704-5	> 0,1 -< 0,5 %	R10 Xn - Harmful; R65 Xi - Irritant; R37 N - Dangerous for the environment; R51, R53	

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

carbon dioxide, foam, powder

Special protection equipment for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products:

Oxides of carbon, oxides of nitrogen, irritating organic vapors., Sulphur oxides

6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

7. Handling and storage

MSDS-No.: 173097 Loctite 640 Page 3 of 5

V001.2

Handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation

Storage:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m ³	Type	Category	Remarks
CUMENE 98-82-8	20	100	Time Weighted Average (TWA).		EU-2000/39/EC
	50	250	Short Term Exposure Limit (STEL):		EU-2000/39/EC
			Skin designation.	Can be absorbed through the skin.	EU-2000/39/EC
	25	125	Time Weighted Average (TWA).		EH40 WEL
	50	250	Short Term Exposure Limit (STEL):		EH40 WEL
			Skin designation.	Can be absorbed through the skin.	EH40 WEL

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

General protection and hygiene measures:

Good industrial hygiene practices should be observed

9. Physical and chemical properties

General characteristics:

Appearance liquid green
Odor: characteristic

Phys./chem. properties:

Flash point $> 100 \,^{\circ}\text{C} (> 212 \,^{\circ}\text{F})$

Vapor pressure < 4 mbar

(20 °C (68 °F))

Density 1,05 g/cm3

()

Solubility (qualitative) not miscible

MSDS-No.: 173097 Loctite 640 Page 4 of 5

V001.2

(Solvent: Water) Solubility (qualitative) (Solvent: Acetone) VOC content

miscible

< 5 % (As defined in the Council Directive 2004/42/EC)

10. Stability and reactivity

Conditions to avoid:

Stable

Materials to avoid:

Reaction with strong acids. Reacts with strong oxidants.

11. Toxicological information

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

Irritating to respiratory system

Skin irritation:

Irritating to the skin

Eye irritation:

Risk of serious damage to eyes

Sensitizing:

May cause sensitization by skin contact.

12. Ecological information

Mobility:

Cured adhesives are immobile.

General ecological information:

Do not empty into drains / surface water / ground water.

Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

13. Disposal considerations

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Waste code():

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

MSDS-No.: 173097 Loctite 640 Page 5 of 5

V001.2

15. Regulations - classification and identification

Indication of danger:

Xi - Irritant



Contains

Hydroxypropyl methacrylate, Acrylic acid

Risk phrases:

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitization by skin contact.

Safety phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water.

S37/39 Wear suitable gloves and eye/face protection.

S51 Use only in well-ventilated areas.

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicted by codes in this safety data sheet are as follows:

R10 Flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R35 Causes severe burns.

R36 Irritating to eyes.

R37 Irritating to respiratory system.

R43 May cause sensitization by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R50 Very toxic to aquatic organisms.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.