

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 11

sds no.: 168434 V002.2

Revision: 15.06.2011

printing date: 17.04.2012

Loctite 326

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

Loctite 326

Relevant identified uses of the substance or mixture and uses advised against:

Intended use:

Acrylics

Details of the supplier of the safety data sheet:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

Ireland

Phone: +353 (14046444) +353 (14519926) Fax-no.:

ua-productsafety.uk@uk.henkel.com

Emergency telephone number:

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

Classification of the substance or mixture:

Classification (DPD):

Xi - Irritant

R36/37/38 Irritating to eyes, respiratory system and skin.

Sensitizing

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

MSDS-No.: 168434 Loctite 326 Page 2 of 11

V002.2

Label elements (DPD):

Xi - Irritant



Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S24 Avoid contact with skin.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water and soap.

S37 Wear suitable gloves.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

2-Hydroxyethyl methacrylate

Other hazards:

None if used properly.

SECTION 3: Composition/information on ingredients

General chemical description:

Acrylate adhesive

MSDS-No.: 168434 Loctite 326 Page 3 of 11

V002.2

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2-Hydroxyethyl methacrylate 868-77-9	212-782-2	> 20- < 30 %	Serious eye irritation 2 H319 Skin irritation 2
			H315
			Skin sensitizer 1
			H317
Isobornyl methacrylate 7534-94-3	231-403-1	> 10-< 20 %	Serious eye irritation 2 H319
			Skin irritation 2 H315
			Specific target organ toxicity - single exposure 3
			H335
Acrylic acid 79-10-7	201-177-9	> 1-< 5 %	Acute toxicity 4; Oral H302
			Skin corrosion 1A
			H314
			Flammable liquids 3
			H226
			Acute toxicity 4; Dermal H312
			Acute hazards to the aquatic environment 1
			H400
			Acute toxicity 4; Inhalation H332
Cumene hydroperoxide 80-15-9	201-254-7	> 0,1-< 0,9 %	Acute toxicity 4; Dermal H312
			Specific target organ toxicity - repeated exposure 2
			H373
			Acute toxicity 3; Inhalation H331
			Acute toxicity 4; Oral H302
			Organic peroxides E H242
			Chronic hazards to the aquatic environment 2 H411
			Skin corrosion 1B H314
Cumene	202-704-5	> 0,1-< 0,3 %	Flammable liquids 3
98-82-8	202 701 3	> 0,1 < 0,5 70	H226
22.02.0			Aspiration hazard 1
			H304
			Specific target organ toxicity - single
			exposure 3
			H335
			Chronic hazards to the aquatic environment 2 H411

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

MSDS-No.: 168434 Loctite 326 Page 4 of 11

V002.2

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
2-Hydroxyethyl methacrylate	212-782-2	> 20 - < 30 %	Xi - Irritant; R36/38
868-77-9			R43
Isobornyl methacrylate	231-403-1	> 10 - < 20 %	N - Dangerous for the environment; R51/53
7534-94-3			Xi - Irritant; R36/37/38
Acrylic acid	201-177-9	> 1 - < 5 %	Xn - Harmful; R20/21/22
79-10-7			R10
			C - Corrosive; R35
			N - Dangerous for the environment; R50
Cumene hydroperoxide	201-254-7	> 0,1 - < 0,9 %	T - Toxic; R23
80-15-9			Xn - Harmful; R21/22, R48/20/22
			O - Oxidizing; R7
			C - Corrosive; R34
			N - Dangerous for the environment; R51, R53
Cumene	202-704-5	> 0,1 - < 0,3 %	R10
98-82-8			Xn - Harmful; R65
			Xi - Irritant; R37
			N - Dangerous for the environment; R51, R53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

Description of first aid measures:

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Most important symptoms and effects, both acute and delayed:

SKIN: Rash, Urticaria.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

SECTION 5: Firefighting measures

Extinguishing media:

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

Special hazards arising from the substance or mixture:

None

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Sulphur oxides

MSDS-No.: 168434 Loctite 326 Page 5 of 11

V002.2

Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact.

See advice in chapter 8

Environmental precautions:

Do not let product enter drains.

Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Chapter 13.

Reference to other sections:

See advice in chapter 8

SECTION 7: Handling and storage

Precautions for safe handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

Conditions for safe storage, including any incompatibilities:

Store in original containers at $8-21^{\circ}C$ (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Specific end use(s):

Acrylics

SECTION 8: Exposure controls/personal protection

Control parameters:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Type	Category	Remarks
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA):		
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8				skin.	
CUMENE			Skin designation:	Can be absorbed through the	ECTLV
98-82-8			-	skin.	
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA):		

Exposure controls:

MSDS-No.: 168434 Loctite 326 Page 6 of 11

V002.2

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties:

Appearance liquid

transparent Amber no valuation

Odor

pН

No data available / Not applicable

Initial boiling point > 149,0 °C (> 300.2 °F)

Flash point > 93,3 °C (> 199.94 °F); Tagliabue closed cup

Decomposition temperature No data available / Not applicable

Vapour pressure < 13 mbar

(26,6 °C (79.9 °F))

Density 1,1 g/cm3

(25 °C (77 °F))

Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Slight

(Solvent: Water)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits Partition coefficient: n-octanol/water No data available / Not applicable No data available / Not applicable Evaporation rate Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

Other information:

No data available / Not applicable

SECTION 10: Stability and reactivity

Reactivity:

Reaction with strong acids.

Reacts with strong oxidants.

MSDS-No.: 168434 Loctite 326 Page 7 of 11

V002.2

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid:

Stable

Incompatible materials:

No data available.

Hazardous decomposition products:

carbon oxides.

SECTION 11: Toxicological information

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

Irritating to respiratory system

Skin irritation:

Irritating to the skin.

Eye irritation:

Irritating to eyes.

Sensitizing:

May cause sensitization by skin contact.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	
80-15-9	LC50	220 ppm	inhalation	4 h	rat	
	LD50	500 mg/kg	dermal		rat	

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide	corrosive		rabbit	
80-15-9				

MSDS-No.: 168434 Loctite 326 Page 8 of 11

V002.2

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	negative positive	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Acrylic acid 79-10-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Harmful to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Mobility:

Cured adhesives are immobile.

MSDS-No.: 168434 Loctite 326 Page 9 of 11

V002.2

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	LC50	227 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
2-Hydroxyethyl methacrylate 868-77-9	EC50	345 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Isobornyl methacrylate 7534-94-3	LC50	1,79 mg/l	Fish	96 h	subcapitata)	Inhibition Test) OECD Guideline 203 (Fish, Acute
Isobornyl methacrylate 7534-94-3	EC50	1,1 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Acrylic acid 79-10-7	LC50	27 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
Acrylic acid 79-10-7	EC50	47 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Acrylic acid 79-10-7	EC50	0,04 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene 98-82-8	LC50	4,8 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute
Cumene 98-82-8	EC50	4 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene 98-82-8	EC50	2,6 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline

Persistence and degradability:

Ī	Hazardous components	Result	Route of	Degradability	Method
	CAS-No.		application		

MSDS-No.: 168434 Loctite 326 Page 10 of 11

V002.2

2-Hydroxyethyl methacrylate	readily biodegradable	aerobic	98 %	OECD Guideline 301 E (Ready
868-77-9				biodegradability: Modified OECD
				Screening Test)
Isobornyl methacrylate			26,8 %	OECD Guideline 301 D (Ready
7534-94-3				Biodegradability: Closed Bottle
				Test)
Acrylic acid	readily biodegradable	aerobic	81 %	OECD Guideline 301 D (Ready
79-10-7				Biodegradability: Closed Bottle
				Test)
Cumene hydroperoxide			18 %	OECD Guideline 301 E (Ready
80-15-9				biodegradability: Modified OECD
				Screening Test)
Cumene		aerobic	86 %	
98-82-8				

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acrylic acid 79-10-7	0,46				25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
Cumene hydroperoxide 80-15-9		9,1				OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2,16					
Cumene 98-82-8 Cumene 98-82-8	3,55	35,5		Carassius auratus	23 °C	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)

SECTION 13: Disposal considerations

Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content

< 3,00 % (As defined in the Council Directive 2004/42/EC)

MSDS-No.: 168434 Loctite 326 Page 11 of 11

V002.2

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R35 Causes severe burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R43 May cause sensitisation by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R50 Very toxic to aquatic organisms.

R51 Toxic to aquatic organisms.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.