

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 10

sds no.: 362964 V002.1

Revision: 06.09.2011

printing date: 17.04.2012

Loctite 330

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier:**

Loctite 330

# Relevant identified uses of the substance or mixture and uses advised against:

Intended use:

Acrylics

# Details of the supplier of the safety data sheet:

Henkel Ireland Limited Product Safety & Regulatory Affairs Tallaght Business Park, Whitestown Dublin 24

Ireland

Phone: +353 (14046444) Fax-no.: +353 (14519926)

ua-productsafety.uk@uk.henkel.com

#### **Emergency Telephone Number:**

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

# Classification of the substance or mixture:

#### Classification (DPD):

Sensitizing

R43 May cause sensitisation by skin contact.

Xi - Irritant

R41 Risk of serious damage to eyes.

R37/38 Irritating to respiratory system and skin.

MSDS-No.: 362964 Loctite 330 Page 2 of 10

V002.1

# Label elements (DPD):

#### Xi - Irritant



#### Risk phrases:

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

#### Safety phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water and soap.

S37/39 Wear suitable gloves and eye/face protection.

S51 Use only in well-ventilated areas.

#### Additional labeling:

Contains epoxy constituents. See information supplied by the manufacturer.

#### Contains:

Methacrylic acid,

Bisphenol-A epichlorhydrin resin MW  $\leq$  700

# Other hazards:

Non corrosive to skin in accordance with the invitro test method, B40 skin corrosion - Human skin model assay, specified in Part B of Annex V to Directive 67/548/EEC.

# **SECTION 3: Composition/information on ingredients**

#### General chemical description:

Dimethacrylate urethane diol based sealant.

MSDS-No.: 362964 Loctite 330 Page 3 of 10

V002.1

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Methacrylic acid 79-41-4	201-204-4	1- 10 %	Acute toxicity 4; Oral H302 Skin corrosion 1A H314 Acute toxicity 4; Dermal H312
2-Ethylhexyl methacrylate 688-84-6	211-708-6	1- 10 %	Serious eye irritation 2 H319 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315
Bisphenol-A epichlorhydrin resin MW <= 700 25068-38-6	500-033-5 01-2119456619-26	1- 5%	Chronic hazards to the aquatic environment 2 H411 Serious eye irritation 2 H319 Skin irritation 2 H315 Skin sensitizer 1 H317
1,3-Butyleneglycol dimethacrylate 1189-08-8	214-711-0	1- 5%	Serious eye irritation 2 H319 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315
Cumene hydroperoxide 80-15-9	201-254-7	0,1- 1%	Acute toxicity 4; Dermal H312 Specific target organ toxicity - repeated exposure 2 H373 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Oral H302 Organic peroxides E H242 Chronic hazards to the aquatic environment 2 H411 Skin corrosion 1B H314

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Tetrahydrofurfuryl methacrylate 2455-24-5	219-529-5	40 - 50 %	Xi - Irritant; R36/37/38
Methacrylic acid 79-41-4	201-204-4	1 - 10 %	C - Corrosive; R35 Xn - Harmful; R21/22
2-Ethylhexyl methacrylate 688-84-6	211-708-6	1 - 10 %	Xi - Irritant; R36/37/38
Bisphenol-A epichlorhydrin resin MW <= 700 25068-38-6	500-033-5 01-2119456619-26	1 - 5 %	R43 Xi - Irritant; R36/38 N - Dangerous for the environment; R51/53
1,3-Butyleneglycol dimethacrylate 1189-08-8	214-711-0	1 - 5 %	Xi - Irritant; R36/37/38
Cumene hydroperoxide 80-15-9	201-254-7	0,1 - 1 %	T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 O - Oxidizing; R7 C - Corrosive; R34 N - Dangerous for the environment; R51/53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

MSDS-No.: 362964 Loctite 330 Page 4 of 10

V002.1

# **SECTION 4: First aid measures**

#### Description of first aid measures:

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.

Skin contact:

Seek medical advice.

Rinse with running water and soap.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Seek medical advice.

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Most important symptoms and effects, both acute and delayed:

SKIN: Rash, Urticaria.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

#### **Extinguishing media:**

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

### Extinguishing media which must not be used for safety reasons:

None known

#### Special hazards arising from the substance or mixture:

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

#### Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

# **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

See advice in chapter 8

### **Environmental precautions:**

Do not let product enter drains.

# Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Wash spillage site thoroughly with soap and water or detergent solution.

Dispose of contaminated material as waste according to Chapter 13.

### Reference to other sections:

See advice in chapter 8

# **SECTION 7: Handling and storage**

MSDS-No.: 362964 Loctite 330 Page 5 of 10

V002.1

#### Precautions for safe handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

#### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

#### Conditions for safe storage, including any incompatibilities:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

#### **Specific end use(s):**

Acrylics

# **SECTION 8: Exposure controls/personal protection**

#### **Control parameters:**

Valid for

Great Britain

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
METHACRYLIC ACID	40	143	Short Term Exposure		EH40 WEL
79-41-4			Limit (STEL):		
METHACRYLIC ACID	20	72	Time Weighted Average		EH40 WEL
79-41-4			(TWA):		

#### **Exposure controls:**

#### Respiratory protection:

Ensure adequate ventilation.

Do not inhale vapors and fumes.

#### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Tightly fitting safety goggles Avoid eye contact.

### Skin protection:

Wear suitable protective clothing.

MSDS-No.: 362964 Loctite 330 Page 6 of 10

V002.1

#### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties:

Appearance liquid

liquid yellow

Odor Acrylic

pH 1

C

Initial boiling point No data available / Not applicable

Flash point  $> 100 \, ^{\circ}\text{C} (> 100 \, 100 \, ^{\circ}\text{C})$ 

Decomposition temperature No data available / Not applicable

Vapour pressure < 4 mbar

Density No data available / Not applicable
Bulk density No data available / Not applicable
Viscosity No data available / Not applicable
Viscosity (kinematic) No data available / Not applicable
Explosive properties No data available / Not applicable

Solubility (qualitative) Slight

(Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

#### Other information:

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

#### Reactivity:

Reaction with strong oxidants.

### **Chemical stability:**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions:

See section reactivity

#### Conditions to avoid:

Stable under normal conditions of storage and use.

#### **Incompatible materials:**

No data available.

# Hazardous decomposition products:

carbon oxides.

# **SECTION 11: Toxicological information**

#### General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### Oral toxicity:

May cause irritation to the digestive tract.

MSDS-No.: 362964 Loctite 330 Page 7 of 10

V002.1

# Inhalative toxicity:

Irritating to respiratory system

#### Skin irritation:

Irritating to the skin.

#### Eye irritation:

The product may cause serious eye damage.

#### Sensitizing:

May cause sensitization by skin contact.

#### Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methacrylic acid 79-41-4	LC50	7,1 mg/l	inhalation	4 h	rat	
2-Ethylhexyl methacrylate 688-84-6	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Cumene hydroperoxide 80-15-9	LD50 LC50 LD50	550 mg/kg 220 ppm 500 mg/kg	oral inhalation dermal	4 h	rat rat rat	

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide	corrosive		rabbit	
80-15-9				

#### Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	

# Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Ethylhexyl methacrylate 688-84-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Bisphenol-A epichlorhydrin resin MW <= 700 25068-38-6	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

# **SECTION 12: Ecological information**

# General ecological information:

Do not empty into drains / surface water / ground water.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

MSDS-No.: 362964 Loctite 330 Page 8 of 10

V002.1

# **Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Tetrahydrofurfuryl methacrylate 2455-24-5	LC50	34,7 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methacrylic acid 79-41-4	LC50	100 - 180 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methacrylic acid 79-41-4	EC50	> 8,2 mg/l	Algae			OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Ethylhexyl methacrylate 688-84-6	LC50	2,78 mg/l	Fish	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Ethylhexyl methacrylate 688-84-6	EC50	4,56 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Ethylhexyl methacrylate 688-84-6	EC50	3,53 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)

# Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Tetrahydrofurfuryl methacrylate 2455-24-5		aerobic	75 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-Ethylhexyl methacrylate 688-84-6	readily biodegradable		88 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Cumene hydroperoxide 80-15-9			18 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

# Bioaccumulative potential / Mobility in soil:

Hazardous components	LogKow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

MSDS-No.: 362964 Loctite 330 Page 9 of 10

V002.1

	Tetrahydrofurfuryl methacrylate 2455-24-5	1,8			
	Methacrylic acid 79-41-4	0,93			
2-E	thylhexyl methacrylate 688-84-6	4,24			
Cı	umene hydroperoxide 80-15-9		9,1		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cı	imene hydroperoxide 80-15-9	2,16			,

# **SECTION 13: Disposal considerations**

#### Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

# **SECTION 14: Transport information**

#### **General information:**

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

# **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content < 9 % (1999/13/EC)

MSDS-No.: 362964 Loctite 330 Page 10 of 10

V002.1

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R35 Causes severe burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R7 May cause fire.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.